



P.C.B LAYOUT TOP VIEW

PIN	φ1.65	φ2.0	φ2.35	φ2.5	
APPD	F	C	H	D	

EATING:DC30V 0.5A
 WITHSTAND VOLTAGE:AC500V(50Hz)/min
 CONTACT RESISTANCE:30mΩ
 INSULATION RESISTANCE:≥ 100MΩ DC250V
 WITHDRAW FORCE:3-20N
 LIFE TEST:5,000cycles

6	PIN	H59 BRSS	1	TIN
5	TERMINAL(LEVEL)	H62 BRSS T=0.3	1	TIN
4	TERMINAL(BEND)	H62 BRSS T=0.3	1	TIN
3	TERMINAL(BEND)	STEEL T=0.2	3	TIN
2	COVER	PPA	1	BLACK
1	BASS	PPA	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATING

RoHS Compliant	HSM 玄茂科技股份有限公司		PART NAME 品名 DC POWER JACK RIGHT ANGLE TYPE PIN OD:??mm NORMAL CLOSE TIN PLATED BLACK COLOR ROHS
	HSUAN MAO TECHNOLOGY CO., LTD.		
APPD. 核准		TOLERANCE 容許公差 0 ± 0.35 .00 ± 0.25 ANG. ± 3°	PART NO. 料號 C9744-XCTB0000R
DWG. 製圖 <i>Helen</i>	SCALE 比例 參考	SIZE. 紙張尺寸 A4	
DATE 制表日 2017/7/19	UNIT 單位 MM	REV. 版本 A	
	PAGE 張數 1 OF 1		