



\* Material: PBT UL 94V-0 Black  
 SPECIFICATIONS  
 \* Current rating: 1A AC DC  
 \* Voltage rating: 100V AC DC  
 \* Temperature range: -25°C~+85°C  
 \* Insulation resistance: 1,000MΩ min.

CIRCUITS	Dim. A	Dim. B	CIRCUITS	Dim. A	Dim. B
8P	3.81	6.21	56P	34.29	36.69
10P	5.08	7.48	58P	35.56	37.96
12P	6.35	8.75	60P	36.83	39.23
14P	7.62	10.02	62P	38.10	40.50
16P	8.89	11.29	64P	39.37	41.77
18P	10.16	12.56	66P	40.64	43.04
20P	11.43	13.83	68P	41.91	44.31
22P	12.70	15.10	70P	43.18	45.58
24P	13.97	16.37	72P	44.45	46.85
26P	15.24	17.64	74P	45.72	48.12
28P	16.51	18.91	76P	46.99	49.39
30P	17.78	20.18	78P	48.26	50.66
32P	19.05	21.45	80P	49.53	51.93
34P	20.32	22.72	82P	50.80	53.20
36P	21.59	23.99	84P	52.07	54.47
38P	22.86	25.26	86P	53.34	55.74
40P	24.13	26.53	88P	54.61	57.01
42P	25.40	27.80	90P	55.88	58.28
44P	26.67	29.07	92P	57.15	59.55
46P	27.94	30.34	94P	58.42	60.82
48P	29.21	31.61	96P	59.69	62.09
50P	30.48	32.88	98P	60.96	63.36
52P	31.75	34.15	100P	62.23	64.63
54P	33.02	35.42			

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准	Betty DATE 制表日 2017/08/18	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 1.27mm FFC/FPC HOUSING DUAL ROW 2XXXP WITHOUT LOCKING RIBS PBT UL94-V0 BLACK INSULATOR ROHS
DWG. 製圖		SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	PART NO. 料號 H1272-XXPNBP00R
			SIZE 紙張尺寸 A 4 REV. 次 A