



■ SPECIFICATIONS

- Voltage rating: 250V AC, DC
- Current rating: 3A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000MΩ min
- Temperature range: -25° C ~ +85° C
- Contact resistance: 15mΩ max

■ HOUSING

- Poles : 08-40P
- Housing Material: PA66 UL94V-0
- The Dimension Marked “▼” Must Be Recorded

Poles	Dimensions (mm)			Poles	Dimensions (mm)		
	A	B	C		A	B	C
2x04	6.00	10.00	8.65	2x13	24.00	28.00	26.65
2x05	8.00	12.00	10.65	2x14	26.00	30.00	28.65
2x06	10.00	14.00	12.65	2x15	28.00	32.00	30.65
2x07	12.00	16.00	14.65	2x16	30.00	34.00	32.65
2x08	14.00	18.00	16.65	2x17	32.00	36.00	34.65
2x09	16.00	20.00	18.65	2x18	34.00	38.00	36.65
2x10	18.00	22.00	20.65	2x19	36.00	40.00	38.65
2x11	20.00	24.00	22.65	2x20	38.00	42.00	40.65
2x12	22.00	26.00	24.65				

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE 0±0.30 0.0±0.25 .00±0.20 .000±0.05 ANGLE. ±1°	PART NAME 品名 PUD 2.0MM HOUSING 2XXXPIN WHITIE COLOR MATERIAL:PA66 UL94V-0 ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 H2019-XXPDW100R
DATE 製表日 2023/07/31	PAGE 張數 1 OF 1	REV. 版次 A	