



SPECIFICATIONS :

Voltage Rating: 250V AC / DC
 Current Rating: 3A AC / DC
 Withstanding Voltage: 1500V AC/minute
 Temperature Range: -25° C~+85° C
 Insulation Resistance: 1000MΩ Min.
 Contact Resistance: 20mΩ Max.

Material: PBT, UL94V-0
 Color: Black

Ordering Information & Dimensions

Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
02	2.54	5.60	12	27.94	31.00
03	5.08	8.14	13	30.48	33.54
04	7.62	10.68	14	32.02	36.08
05	10.16	13.22	15	35.56	38.62
06	12.70	15.76	16	38.10	41.16
07	15.24	18.30	17	40.64	43.70
08	17.78	20.84	18	43.18	46.24
09	20.32	23.38	19	45.72	48.78
10	22.86	25.92	20	48.26	51.32
11	25.40	28.46	21	50.80	53.86
			22	53.34	56.40

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	一般公差 GENERAL TOLERANCE . X ±0.3 . XX ±0.2 . XXX ±0.1 SIZE. 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 2.54mm HOUSING SINGLE ROW 1XXXPIN BLACK INSULATOR ROHS PART NO. 料號 H2420-XXPSB000R
DATE 制表日 2022/11/28			