



■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating : 3A AC / DC
- Withstanding voltage: 1500V AC/minute
- Temperature range : -25°C~+85°C
- Insulation resistance : ≥1000MΩ
- Contact resistance : ≤20mΩ
- After environmental testing : ≤30mΩ
- Material : PBT UL94V-0
- Packing : 1000pcs/ Bag

Poles	Dimensions (mm)	
	A	B
6	5.08	7.62
8	7.62	10.16
10	10.16	12.70
12	12.70	15.24
14	15.24	17.78
16	17.78	20.32
18	20.32	22.86
20	22.86	25.40
22	25.40	27.94
24	27.94	30.48
26	30.48	33.02
28	33.02	35.56
30	35.56	38.10
32	38.10	40.64
34	40.64	43.18
36	43.18	45.72
38	45.72	48.26
40	48.26	50.80
42	50.80	53.34
44	53.34	55.88
46	55.88	58.42
48	58.42	60.96
50	60.96	63.50
52	63.50	66.04
54	66.04	68.58
56	68.58	71.12
58	71.12	73.66
60	73.66	76.20
62	76.20	78.74
64	78.74	81.28

<p>RoHS Compliant</p>		<p><b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 HELEN</p>	<p>SCALE 比例 參 考</p>	<p>一般公差 GENERAL TOLERANCE .X ±0.3 .XX ±0.2 .XXX ±0.1</p>	<p>PART NAME 品 名 2.54mm HOUSING 2XXXP DUAL ROW WITH LOCKING RIB BLACK INSULATOR ROHS</p>
<p>DWG. 製圖 ABBY</p>	<p>UNIT 單位 M M</p>	<p>SIZE. 紙張尺寸 A 4</p>	<p>PART NO. 料 號 H2580-XXPDYB00R</p>
<p>DATE 制表日 2022/02/21</p>	<p>PAGE 張數 1 OF 1</p>	<p>REV. 版 次 C</p>	