



Specification:

- 1、Material: Rubber shell:PA66 UL94V-0
- 2、Current rating: 20A max
- 3、Voltage rating: 300V AC/DC
- 4、Temperature range:-25°C to +85°C
- 5、Contact resistance: $\leq 10\text{m}\Omega$
- 6、Insulation resistance: $\geq 1000\text{M}\Omega$
- 7、Withstand voltage: 2000V AC/minute
- 8、Fixing force of pins: $\geq 25\text{N}$
- 9、Applicable PC board thickness: 1.6mm

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	<i>Helen</i>	0 ± 0.4 .00 ± 0.35 ANG. $\pm 5^\circ$	6.2MM MALE HOUSING DUAL ROW 2X2PIN WITH LOCKING RIBS WHITE COLOR MATERIAL: NYLON66 UL94V-0 ROHS
DATE 制表日	UNIT 單位	SIZE 紙張尺寸	PART NO.
2022/5/20	M M	A 4	H6211-04PDYW10R
	PAGE 張數	REV. 版本	料號
	1 OF 1	A	