



DIMENSION:(MM)

MATERIAL:BRASS
 THICKNESS:0.25
 HARDNESS:SH
 PLATING:TIN 40u' MIN.
 INSULATION O.D.:2.3 MAX.
 WIRE RANGE:(AWG)16-22
 VOLTAGE RATING:AC/250V,DC/350V
 CURRENT RATING:AC,DC,10A
 TEMPERATURE RANGE : -25°C TO +85°C
 MATE:0.5 THICKNESS PIN

T:0.25 ± 0.03
 L:15.6 ± 0.35
 E:6.2 ± 0.25
 W:3.75 ± 0.2
 IS:3.75 ± 0.3
 WS:2.4 ± 0.3
 H:4.0 ± 0.25
 H1:2.8 ± 0.25
 H2:1.85 ± 0.15
 e:3.6 ± 0.25
 t:1.05 ± 0.25

APPD. 核准 HELEN DWG. 製圖 ABBY DATE 制表日 2013/05/16		RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		TOLERANCE 容許公差 .0 ± .00 ± ANG ±	PART NAME 品名 110 TERMINAL FEMALE MATERIAL:BRASS TIN PLATED SUITABLE FOR 16-20AWG 5K/ROLL ROHS
SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1		TOLERANCE 容許公差 .0 ± .00 ± ANG ±	SIZE. 紙張尺寸 A4 REV. 版次 A	PART NO. 料號 T1101-TBY00001R		