



DIMENSION:(MM)

- T:0.25 ± 0.03
- L:22.3 ± 0.35
- IS:4.2 ± 0.35
- WS:3.3 ± 0.35
- H:3.4 ± 0.35
- H1:3.2 ± 0.35
- H2:1.2 ± 0.25
- D:∅2.25 ± 0.1
- D1:∅3.2 ± 0.15
- W:4.4 ± 0.3
- W1:3.6 ± 0.25
- e:8.6 ± 0.25
- e1:3.5 ± 0.25

MATERIAL:BRASS
 THICKNESS:0.25
 HARDNESS:SH
 PLATING:TIN 40u' MIN
 WIRE RANGE:(AWG)18-22
 INSULATION O.D.:3.8 MAX.
 RATED VOLTAGE:AC/250V,DC/350V
 CURRENT RATED:AC,DC,10A
 TEMPERATURE RANGE : -25°C TO +85°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE 容許公差 .0 ± .00 ± ANG ±	PART NAME 品名 ∅2.36mm TERMINAL BRASS MATERIAL TIN PLATING AWG18-22 1ROLL=5000 PCS ROHS
DWG. 製圖 ABBY		UNIT 單位 MM	
DATE 制表日 2013/11/11	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 T2030-TBD00000R