



MATERIAL:BRASS

THICKNESS:0.25

HARDNESS:SH

PLATING:TIN 40u' MIN

WIRE RANGE:(AWG)14-18

INSULATION O.D.:3.8 MAX.

VOLTAGE RATING:AC/250V,DC/350V

CURRENT RATING:AC,DC,10A

TEMPERATURE RANGE : -25°C TO +85°C

DIMENSION:(MM)

T:0.25 ± 0.03

L:20.5 ± 0.35

E:13.3 ± 0.25

W:3.6 ± 0.25

W1:4.5 ± 0.25

IS:5.0 ± 0.3

WS:3.3 ± 0.3

H:4.9 ± 0.3

H1:3.6 ± 0.3

D:3.2 ± 0.1

D1:2.0 ± 0.06

e:8.6 ± 0.3

| | | | | |
|------------------------|--|-------------------|--------------------------------------|---|
| APPD. 核准 Helen | | SCALE 比例 参考 | TOLERANCE 容許公差 .00 ± ANG. ± | PART NAME 品名 JST 2.0mm FEMALE TERIMNAL BRASS MATERIAL TIN PLATING AWG14~18 ROHS |
| DWG. 製圖 Yumi | | | | |
| DATE 制表日 2011/01/26 | | PAGE 張數 1 OF 1 | REV. 版次 A | PART NO. 料號 T2120-TBA00000R |

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.