



DIMENSION:(MM)
 T:0.25 ±0.03
 L:22.0 ±0.3
 E:11.2 ±0.4
 IS:4.9 ±0.3
 WS:3.3 ±0.3
 H:4.7 ±0.25
 H1:3.1 ±0.25
 H2:1.2 ±0.25
 W:3.0 ±0.15
 W1:3.6 ±0.25
 W2:4.2 ±0.3
 D:3.05-3.15
 D1:2.65-2.8
 e:8.4 ±0.25

MATERIAL:BRASS
 THICKNESS:0.25
 HARDNESS:SH
 PLATING:TIN 40u' MIN
 WIRE RANGE:(AWG)14-18
 INSULATION O.D.:3.8 MAX.
 VOLTAGE RATING:AC/250V,DC/350V
 CURRENT RATING:AC,DC,15A
 TEMPERATURE RANGE : -25°C TO +85°C

APPD. 核准 Angel			RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
DWG. 製圖 Yumi			TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 MX φ2.36mm FEMALE TERMINAL BRASS MATERIAL TIN PLATING AWG14~18 ROHS LOW-LEAD		PART NO. 料號 T2130-TBA00000R
DATE 制表日 2009/09/24		SCALE 比例 參考	UNIT 單位 M M	SIZE. 紙張尺寸 A 4		
PAGE 張數 1 OF 1		REV. 版次 A				