



DIMENSION(MM)

MATERIAL:BRASS  
 THICKNESS:0.3  
 HARDNESS:SH  
 PLATING:TIN 40u' MIN.  
 INSULATION O.D.:3.8MAX.  
 WIRE RANGE:(AWG)14-20  
 VOLTAGE RATING:AC/250V,DC/350V  
 CURRENT RATING:AC,DC,15A  
 TEMPERATURE RANGE : -25°C TO +85°C  
 MATE:0.8 THICKNESS PIN

T:0.3±0.03  
 L:19.2±0.35  
 E:7.7±0.25  
 W:7.4±0.2  
 IS:4.9±0.35  
 WS:3.2±0.35  
 H:4.9±0.25  
 H1:3.2±0.25  
 H2:2.9±0.15  
 t:4.2±<sup>0.35</sup>/<sub>0.5</sub>

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	 TOLERANCE 容許公差 .0 ± .00 ± ANG. ± SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1 REV. 版次 A	PART NAME 品名 250 Type FEMALE TERMINALS WITH LOCK TYPE	
DWG. 製圖 Betty		WIRE RANGE:14~20AWG MATERIAL:BRASS PLATING:TIN FOR TAB 6.3*0.8mm ROHS	
DATE 制表日 2013/04/19	PART NO. 料號 T2521-TBR00000R		