



**Specifications & Ordering Information:**

Thickness	Material	Wire Range	Insulation O.D.	Finish	Qty/reel
0.2	Phosphor Bronze	AWG #24~28	1.4-1.1mm	T:TIN PLATED	15,000pcs
				S:SELECTIVE GOLD PLATED	
				G:GOLD FLASH PLATED	
				H:SELECTIVE GOLD 15u" PLATED	

**Plating Notes:**

- "T" Tin plating: 60u" Tin over 50u" Nickel on entire contact.
- "S" Selective gold plating: 0.6~0.8u" gold on contact area, all over Nickel on entire contact.
- "G" Gold Flash plating: 0.6~0.8u" all over Nickel on entire contact.
- "H" Selective gold plating 15u": 15u" gold on contact area, all over Nickel on entire contact.

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 <b>HELEN</b> DATE 制表日 2019/3/15		TOLERANCE 容許公差 0 ± 0.25 .00 ± 0.13 ANG. ± UNIT 單位 M M PAGE 張數 1 OF 1 REV. 版本 B	PART NAME 品名 2.54mm TERMINAL PHOSPHOR BRONZE MATERIAL 24~28AWG 1ROLL=15000PCS ROHS LOW-LEAD PART NO. 料號 T7058-XPL00000R