



Specifications:

Current Rating:1A AC, DC

Voltage Rating:50V AC, DC

Operating Temp:-25°C~+85°C

Contact Resistance:30mΩ Max

Insulation Resistance:100MΩ Min.

Dielectric Withstanding Voltage:500V AC/min

MAT'L:PHOSPHOR BRONZE
 TREATMENT:GOLD FLASH OR TIN PLATED(AFTER)
 WIRE RANGE:SUITABLE FOR AWG#28~32

RoHS Compliant		HSM 玄茂科技股份有限公司		HSUAN MAO TECHNOLOGY CO., LTD.												
APPD. 核准	Hedy		<table border="1"> <tr> <th colspan="2">TOLERANCE</th> </tr> <tr> <td>TYPE</td> <td>±0.4 ±0.5</td> </tr> <tr> <td>PARTIAL</td> <td>20-40 40 UP</td> </tr> <tr> <td>TYPE</td> <td>±0.2 ±0.3</td> </tr> <tr> <td>PARTIAL</td> <td>1-10 10-20</td> </tr> </table>		TOLERANCE		TYPE	±0.4 ±0.5	PARTIAL	20-40 40 UP	TYPE	±0.2 ±0.3	PARTIAL	1-10 10-20	PART NAME 品名	
TOLERANCE																
TYPE	±0.4 ±0.5															
PARTIAL	20-40 40 UP															
TYPE	±0.2 ±0.3															
PARTIAL	1-10 10-20															
DWG. 製圖		SCALE 比例	參考	1.0mm TERMINAL TIN PLATED PHOSPHOR BRONZE MATERIAL SUITABLE FOR AWG28~32 ROHS												
DATE 制表日	2020/7/31	UNIT 單位	MM	SIZE 紙張尺寸	A 4											
		PAGE 張數	1 / 1	REV. 版次	A											
			PART NO.		料號 T9017-TPP00000R											