



■ SPECIFICATIONS

- Rated Voltage : 125 V AC/DC
- Current Rating : 3A AC/DC.
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 1,000MΩ min.
- Temperature Range : - 40°C to + 105°C
- Contact resistance : 20mΩ max.

■ WAFER

- ① Poles No : 2~15
- ② Base : 9T:PA9T UL94 V-0 (Nature)

Material : 1. Contact : PhosphorBronze/Matte Sn
 2. Base : Refer the above options
 3 Solder tabs:PhosphorBronze/Matte Sn

• Package: Reel

PIN.	Dimension(mm)		
	A	B	C
2	2.00	8.00	4.80
3	4.00	10.00	6.80
4	6.00	12.00	8.80
5	8.00	14.00	10.80
6	10.00	16.00	12.80
7	12.00	18.00	14.80
8	14.00	20.00	16.80
9	16.00	22.00	18.80
10	18.00	24.00	20.80
11	20.00	26.00	22.80
12	22.00	28.00	24.80
13	24.00	30.00	26.80
14	26.00	32.00	28.80
15	28.00	34.00	30.80

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 參考	TOLERANCE .0 ±0.30 .00 ±0.20 .000 ±0.10	PART NAME 品名 2.0MM WAFER 1XXXPIN SMT RIGHT ANGLE TYPE MATTE TIN PLATING MATERIAL:PA9T UL94V-0 WHITE INSULATOR REEL PACKING ROHS
DWG. 製圖 Betty	UNIT 單位 MM	ANGLE 0° ±1°	
DATE 制表日 2023/08/22	PAGE 張數 1 OF 1	SIZE. 紙張尺寸 A 4	PART NO. 料號 W2041-XXPBZBCRR

0.1 MAX