



- Specifications(规格):
- Voltage rating(额定电压): 125V AC / DC
 - Current rating(额定电流): 2A AC / DC
 - Withstanding voltage(耐压值): 1000V AC/minute
 - Temperature range(工作温度): -40°C~+105°C
 - Insulation resistance(绝缘电阻): ≥1000MΩ
 - Contact resistance(接触电阻): ≤20mΩ
 - After environmental testing(环境测试后): ≤30mΩ

Nylon 66 UL 94V-0	Brass	Tin-Plated	1,000Pcs
Material	Material(Pin)	Finish(Pin)	Q' ty/Bag

Poles	Dimensions(mm)					
	A	B	C	D	E	F
2	2.00	5.30	7.70			
3	4.00	7.30	9.70			
4	6.00	9.30	10.30	6.00	4.25	6.70
5	8.00	11.30	12.30	8.00	4.25	7.00
6	10.00	13.30	14.30	10.00	4.25	7.00
7	12.00	15.30	16.30	12.00	4.25	7.00
8	14.00	17.30	18.30	14.00	8.25	11.00
9	16.00	19.10	20.30	16.00	8.25	11.00
10	18.00	21.30	22.30	18.00	8.25	11.00
11	20.00	23.30	24.30	20.00	8.25	11.00
12	22.00	25.30	26.30	22.00	8.25	11.00
13	24.00	27.30	28.30	24.00	8.25	11.00
14	26.00	29.30	30.30	26.00	8.25	11.00
15	28.00	31.30	32.30	28.00	8.25	11.00
16	30.00	33.30	34.30	30.00	8.25	11.00
17	32.00	35.30	36.30	32.00	8.25	11.00
18	34.00	37.30	38.30	34.00	8.25	11.00
19	36.00	39.30	40.30	36.00	8.25	11.00
20	38.00	41.30	42.30	38.00	8.25	11.00

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	SCALE 比例	一般公差 GENERAL TOLERANCE .X ±0.3 .XX ±0.2 .XXX ±0.1	PART NAME 品名 2.0 WAFER 1XXXPIN RIGHT ANGLE TYPE TIN PLATING DIP LENGTH:2.5mm OR 3.2mm BEIGE COLOR NYLON66 UL94V-0 BAG PACKING ROHS
DWG. 製圖	UNIT 單位	SIZE. 紙張尺寸	PART NO.
DATE 制表日	PAGE 張數	REV. 版次	料號
2018/05/04	1 OF 1	A	W2102-XXPRTC1(B,C)GR