



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 300V AC, DC
- 3、Temperatuer Range: -40℃~+105℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1700V AC/minute
- 7、Material: Wafer LCP, UL94V-0  
PIN Phosphoric bronze Tin-plated  
Solder tad Phosphoric bronze Tin-plated

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准		<b>TOLERANCE</b> 零件公差	<b>PART NAME</b> 品名
DWG. 製圖 <i>Helen</i>	<b>SCALE</b> 比例 參考	0 ± 0.35 .00 ± 0.25 ANG. ± 5°	4.0mm LED Light Bar Wafer 2Pin Male SMT Right Angle Type Tin Plating Beige Color Reel Packing ROHS
DATE 制表日 2022/7/5	<b>UNIT</b> 單位 M M	<b>SIZE</b> 紙張尺寸 A 4	<b>PART NO.</b> 料號 W2208-02MBTCR0R
	<b>PAGE</b> 張數 1 OF 1	<b>REV.</b> 版本 A	