



### SPECIFICATIONS

#### Electrical

- Current Rating: 5A AC, DC
- Voltage Rating: 250V AC, DC
- Operating Temp.: -25°C ~ +85°C
- Insulation Resistance: 1000MΩ/ min.
- Dielectric Withstanding Voltage: 1500V AC/ min.
- Contact Resistance: 10mΩ/ max.

#### Material

Material: Nylon66, UL94V-2

Poles	Dimension mm (in.)	
	A	B
2	3.96	8.00
3	7.92	12.00
4	11.88	15.90
5	15.84	20.00
6	19.80	24.00
7	23.76	27.90
8	27.72	31.90
9	31.86	35.80
10	35.64	39.90
11	39.60	43.90
12	43.56	47.80
16	59.40	63.80

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 HELEN DATE 制表日 2022/8/17	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± 0.35 .00 ± 0.3 ANG. ± SIZE. 紙張尺寸 A4 REV. 版本 C	PART NAME 品名 3.96mm WAFER RIGHT ANGLE TYPE XXP W/O LOCKING RIBS TIN PLATED WHITE COLOR ROHS PART NO. 料號 W2400-XXPRNTWOR