



SPECIFICATIONS

Electrical

Current Rating: 5A AC, DC
 Voltage Rating: 250V AC, DC
 Operating Temp.: -25°C ~ +85°C
 Insulation Resistance: 1000MΩ/ min.
 Dielectric Withstanding Voltage: 1500V AC/ min.
 Contact Resistance: 10mΩ/ max.

Material

Material: Nylon66, UL94V-2
 Terminal Material: Brass/ Tin-plated

Poles	Dimension mm (in.)	
	A	B
2	3.96	7.92
3	7.92	11.88
4	11.88	15.84
5	15.84	19.80
6	19.80	23.76
7	23.76	27.72
8	27.72	31.68
9	31.86	35.64
10	35.64	39.60
11	39.60	43.56
12	43.56	47.52

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 參考	TOLERANCE 容許公差 .0 ± 0.5 .00 ± 0.35 ANG. ±	PART NAME 品名 3.96mm WAFER RIGHT ANGLE TYPE 1XXXP WITH LOCKING RIBS TIN PLATED WHITE COLOR ROHS
DWG. 製圖 Helen	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 W2400-XXPRYTWOR
DATE 制表日 2022/8/17	PAGE 張數 1 OF 1	REV. 版次 C	