


Pos.	A	B
06	23.76	19.80
12	47.52	43.56

Material and Finish	Electrical Characteristics	Mechanical Characteristics
1. Housing: Thermoplastic (UL94V-2), White. 2. Terminal: Copper Alloy, Tin Plating.	1. Current Rating: 5.0 Amp. Max. 2. Dielectric Withstand Voltage: 1000V AC RMS for One Minute. 3. Insulation Resistance: 1000M Ohms Min. at 1000V DC.	1. Operating Temperature: -20°C ~ +85°C

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 <b>BETTY</b>		<i>Tolerance</i> 0.0 ±0.30 0.00 ±0.20 0.000 ±0.10	<b>PART NAME 品名</b> 3.96mm POWER PLUG XXP STRAIGHT TYPE W/O PEGS WHITE INSULATOR ROHS
DWG. 製圖 <b>BETTY</b>	SCALE 比例 參考	UNIT 單位 M M	<b>PART NO.</b> <b>料號</b> W2460-XXPSNTW0R
DATE 制表日	PAGE 張數 1 OF 1	REV. 版本 A	

