

# FEATURES AND SPECIFICATIONS

## Features and Benefits

Size 2 to 12 circuits

## Electrical


- Current Rating: 3A AC, DC
- Voltage Rating: 250V AC/ max.
- Insulation Resistance: 1000MΩ/ min.
- Dielectric Withstanding Voltage: 1500V AC/ min.
- Contact Resistance: 10mΩ/ max.
- Operating Temp.: -25°C ~ +85°C

## Physical

- Material: Nylon 66, UL94V-2
- Terminal Material: Brass/ Tin-plated

Poles	Dimension mm (in.)	
	A	B
2	2.54(0.100)	5.12(0.202)
3	5.08(0.200)	7.66(0.302)
4	7.62(0.300)	10.20(0.402)
5	10.16(0.400)	12.74(0.502)
6	12.70(0.500)	15.30(0.602)
7	15.24(0.600)	17.94(0.706)
8	17.78(0.700)	20.48(0.806)
9	20.32(0.800)	23.02(0.906)
10	22.86(0.900)	25.58(1.007)
11	25.40(1.000)	28.12(1.107)
12	27.94(1.100)	30.68(1.208)

NOTE:  
TOLERANCE:  
2P~9P ±0.20  
10~12P ±0.30

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 <b>HELEN</b>		TOLERANCE 容許公差 .0 ±0.35 .00 ±0.25 ANG ±	PART NAME 品名 2.54mm WAFER XXP REVERSE RIGHT ANGLE TYPE BEIGE COLOR(V2) WITH LOCKING RIBS TIN PLATED ROHS
DWG. 製圖 <b>ABBY</b>	SCALE 比例 參考	UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 制表日 2016/12/27	PAGE 張數 1 OF 1	REV. 版次 B	PART NO. 料號 <b>W2600-XXPCYT0R</b>