



Specifications

Voltage Rating: 250V AC/ DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1500V AC/Minute
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25° C~+85° C
 Contact Resistance: 20mΩ Max.
 Pin Material: Brass/Gold-flash or Tin-plated
 Material: PBT,UL94V-0
 Q'ty/Bag: 1000PCS

Ordering Information & Dimensions

Poles	Dimensions (mm)	
	A	B
6	5.08	10.20
8	7.62	12.70
10	10.16	15.20
12	12.70	17.80
14	15.24	20.30
16	17.78	22.90
18	20.32	25.40
20	22.86	27.90
22	25.40	30.50
24	27.94	33.00
26	30.48	35.60
28	33.02	38.10
30	35.56	40.60
32	38.10	43.20
34	40.64	45.70
36	43.18	48.30
38	45.72	50.80
40	48.26	53.30

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	一般公差 GENERAL TOLERANCE .X ±0.3 .XX ±0.2 .XXX ±0.1	PART NAME 品名 2.54mm Wafer 2XXXP RIGHT ANGLE TYPE WITH LOCKING RIB WITH KINK PIN BLACK COLOR ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 W2680-XXPRXYBKR
DATE 制表日 2013/08/13	PAGE 張數 1 OF 1	REV. 版次 A	