


NOTE:

- 1. MATERIAL:
 - INSULATOR: PA9T UL94V-0, BLACK.
 - PWR & GND PIN: C1100
 - SENSE PIN: C2680
 - BOARD LOCK: SUS201
- 2. FINISH:
 - CONTACT: 80u" Min MATTE TIN PLATED OVERALL, 30u" Min NICKEL UNDER PLATED.
- 3. ELECTRICAL CHARACTERISTICS:
 - CURRENT RATING: 9.2A PER PIN(PWR & GND PIN)
 - DIELECTRIC WITHSTANDING VOLTAGE: 1500 VAC 1 MINUTE
 - INSULATION RESISTANCE: 1000MΩ MIN. AT 500V/DC
 - CONTACT RESISTANCE: 10mΩ MAX
 - TEMPERATURE RANGE: -40° C~+105° C
- 4. MAX. PROCESSING TEMP: 230° C FOR 60 SECONDS.
260° C FOR 10 SECONDS.



PIN SIGNAL	PIN NO.
PWR PIN	1~6
GND PIN	7~12
S1	CARD_PWR_STABLE
S2	CARD_CBL_PRES#
S3	SENSE0
S4	DO NOT USE

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE 0 ± 0.30 .0 ± 0.25 .00 ± 0.20 .000 ± 0.05 ANGLE: ± 1°	PART NAME 品名 3.0MM PCI-E FEMALE WAFER 12+4PIN 90° MATTE TIN PLATING DIP LENGTH:2.1MM MATERIAL:PA9T UL94V-0 BLACK COLOR REEL PACKING ROHS
DWG. 製圖	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO. W4234-16PRZABBRR
DATE 製表日 2024/03/20	PAGE 張數 1 OF 1	REV. 版次 A	料號

RECOMMEND P.C.B LAYOUT
TOLERANCE: ±0.05 (TOP VIEW)