



P.C.B LAYOUT

SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material:LCP
 Pin Material: Phosphor Bronze
 Solder Tabs: Brass/Matte Tin-plated or Gold-flash

Circuit No.	Dimensions		
	A	B	C
02P	2.50	10.00	6.00
03P	5.00	12.50	8.50
04P	7.50	15.00	11.00
05P	10.00	17.50	13.50
06P	12.50	20.00	16.00
07P	15.00	22.50	18.50
08P	17.50	25.00	21.00
09P	20.00	27.50	23.50
10P	22.50	30.00	26.00

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准
 DWG. 製圖 Helen
 DATE 制表日 2022/12/13

SCALE 比例 參考
 UNIT 單位 MM
 PAGE 張數 1 OF 1

TOLERANCE 容許公差
 0 ± 0.35
 .00 ± 0.25
 ANG. ± 5°
 SIZE 紙張尺寸 A4
 REV. 版本 A

PART NAME 品名
 2.5mm WAFER 1XXXP SMT STRAIGHT TYPE
 MATERIAL:LCP WHITE COLOR
 WITHOUT KINK ROHS

PART NO.
 料號 W7600-XXPANXWXN